

[ENQUIRY \(/GENQUIRY.PHP\)](#)[TESTIMONIALS \(/TESTIMONIALS.PHP\)](#)[CAREERS \(/CAREER.PHP\)](#)[INDIA RESELLERS \(/AUTHORIZED-RESELLERS.PHP\)](#)[GULF RESELLERS \(/GULF-RESELLERS.PHP\)](#)

(/)

[ABOUT US \(ABOUT.PHP\)](#)[PRODUCTS](#)[CERTIFICATIONS \(/CERTIFICATIONS.PHP\)](#)[TRADE SHOWS \(/TRADE-SHOWS.PHP\)](#)[CONTACT \(/CONTACT.PHP\)](#)

# Terminations

[Home](#) / [Heat Shrink](#) / [Cable Terminations](#) / [Heat Shrinkable Terminations for Low Tension PVC/XLPE/PILC](#)

## Heat Shrinkable Terminations for Low Tension PVC/XLPE/PILC

**XSE/O (LT) - PSE/O (LT)**

### Features

- All key inputs are produced in-house.
- Corrosion resistant and unlimited shelf life..
- In compliance with EN-50393 / IS-13573-1.
- Electrolytic grade connectors.

### Heat Shrink Terminations

Heat Shrinkable Terminations for Low Tension PVC/XLPE/PILC ([heat-shrinkable-terminations-for-low-tensionpvcxlpepilc.php](#))

Heat Shrinkable Terminations upto 15 kV for PILC Cables (BELTED) ([heat-shrinkable-terminations-3-core-pilc-belted.php](#))

Heat Shrinkable Terminations upto 36 kV For 3 Core XLPE/EPR Insulated Cable ([heat-shrinkable-terminations-36kv-3-core-xlpe-epr.php](#))

Heat Shrinkable Terminations upto 36 kV for PILC Cables ([terminations-upto-36-kv-for-pilc-cables.php](#))

Heat Shrinkable Terminations upto 36 kV (For Single Core Aerial Bunched Cable) ([heat-shrinkable-](#)



Heat Shrinkable Terminations PVC/XLPE 1.1 kV



Heat Shrinkable Termination PILC 1.1 kV

[terminations-36kv-aerial-bunched-cables.php](#)

[Heat Shrinkable Terminations for 72.5 kV \(For Single Core XLPE Cable\) \(heat-shrinkable-terminations-single-core-xlpe-cables.php\)](#)

[Heat Shrinkable Terminations upto 36 kV For Single Core XLPE/EPR Insulated \(heat-shrinkable-terminations-36kv-single-core-xlpe-epr.php\)](#)

## Heat Shrinkable Terminations for Low Tension PVC/XLPE/PILC

Product Code: XSE/O (LT) - PSE/O (LT)

<b>1.1 kV, PVC/XLPE Indoor Terminations</b>	<b>Cable Cross Section (mm<sup>2</sup>)</b>	<b>Type No.</b>
	4 x 16 - 35	XSE - 01
	4 x 50 - 95	XSE - 02
	4 x 120 - 185	XSE - 03
	4 x 225 - 300	XSE - 04
<b>1.1 kV, PVC/XLPE Outdoor Terminations</b>	<b>Cable Cross Section (mm<sup>2</sup>)</b>	<b>Type No.</b>
	4 x 16 - 35	XSO - 01
	4 x 50 - 95	XSO - 02
	4 x 120 - 185	XSO - 03
	4 x 225 - 300	XSO - 04
<b>1.1 kV, PILC Indoor Terminations</b>	<b>Cable Cross Section (mm<sup>2</sup>)</b>	<b>Type No.</b>
	4 x 16 - 35	PSE - 01
	4 x 50 - 95	PSE - 02
	4 x 120 - 185	PSE - 03
	4 x 225 - 300	PSE - 04
<b>1.1 kV, PILC Outdoor Terminations</b>	<b>Cable Cross Section (mm<sup>2</sup>)</b>	<b>Type No.</b>
	4 x 16 - 35	PSO - 01
	4 x 50 - 95	PSO - 02
	4 x 120 - 185	PSO - 03
	4 x 225 - 300	PSO - 04